



- Bucket Full Indicator Avoids Overflows
- 3 Modes – Auto, Continuous, Manual
- 3 Fan Speeds – High, Low, Auto
- Low-temperature Operation (38°F)



Built-in Pump for Easy Draining
Built-in pump and quick-connect water hose included to discharge the water into a sink or basement window.



Energy Efficient
Energy Star means its more energy efficient and helps reduce your utility bill.



Filter Indicator
Washable filter helps to reduce bacteria, odors, and particles.



Warranty
Two (2) years Parts & Labor

Control Humidity - Helps keep your home conveniently dry, fresh, and quiet

The Hisense HT5021KP Energy Star 50* Pint 3-Speed Dehumidifier has a built-in pump that can quietly discharge water out a basement window or into a sink using the included quick-connect hose. Reliable and eco-friendly this dehumidifier can operate at temperatures as low as 38°F. Three operating modes (manual set, continuous, and auto dry) and the very low sound level make this a versatile choice. Additional features include a programmable 24-hour on/off timer, adjustable humidistat, and full-tank alert/shutoff.

TECHNICAL SPECIFICATIONS

TECHNICAL SPECIFICATIONS	
Performance	
Model #	HT5021KP
Dehumidification(Pints/24 hours)	50
Heating Capacity	N/A
Coverage	Up to 4500 sq ft
Refrigerant	R-410A
Noise Level in dB(A)	48-50 dB(A)
Electrical	
Voltage / Freq / Amps	115V / 60Hz, 7.8A* / 4.9A
General Features	
Unit Control Type	Electronic
Fan Control	Button
Adj. Humidity Control	Yes
Display Type	LED
Continuous Run	Yes
Auto Dry	Yes
Manual Setting	30% - 80%
Timer-Clock	Yes
Fan Speeds	3 Speeds (Lo, Hi, Auto)
Pump Mode	No
Refrigeration Compartment	
Auto Bucket Shutoff	Yes
Garden Hose Connection	Standard Garden Hose
Washable Filters	Yes
Max Pump Discharge Height	16 feet (head)
Accessories	
Quick Connect Hose	Yes. included (9mm dia.)
Approvals	
Safety	UL
Energy	Energy Star
Shipping	
Unit Dimension WxDxH (mm)	387 X 300 X 628

Net Weight (Kg)	19.5
Unit Dimension WxDxH (inch)	15.2 X 11.8 X 24.7
Net Weight (lbs)	43
Product	
Parts & Labor	2 years
UPC	819130028927

Note:

*: Rated Amps(A) / accorded UL 60335 Safety

Product Images

Control Panel



Draining hose with Quick Connector (included)



All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise. ©2020 Hisense USA, All rights reserved

Hisense USA Corporation
 7310 McGinnis Ferry Road, Suwanee, GA, 30024
 1-888-935-8880
www.hisense-usa.com