

# Hisense

## 70 PINT

up to 500 sq.ft

**DEHUMIDIFIER BUILT-IN PUMP**

### Model: DH-70KP1SDLE

- Built-in Pump, quick-connect hose included
- 3 Modes - Auto, Continuous, Manual
- 2 Fan Speeds
- Low-temperature Operation (38 deg F)



#### Bucket full indicator

Avoids overflow and reminds you when the bucket is full



#### Filter Indicator

Washable filter helps to reduce bacteria, odors and particles



#### Electronic Control

Electronic push-button controls with digital LED display



#### Warranty

2 Years Parts & Labor

## Cool Comfort - Built-in Pump helps keep your home dry and fresh, without having to empty the bucket

The Hisense DH-70KP1SDLE Energy Star 70-Pint 2-Speed Dehumidifier has a built-in pump that pumps the water upward to continuously drain out a basement window or into a sink using the included quick-connect hose. The unit is an affordable and eco-friendly dehumidifier removing 70 pints of damaging moisture per day, operating at temperatures as low as 38 degrees Fahrenheit. Three operating modes (manual set, continuous and auto dry) make this Energy Star unit a versatile choice. During dehumidification, water accumulates in the internal water tank or is continuously pumped into a drain using the included hose. Additional features include a programmable 24-hour on/off timer, adjustable humidistat, and full-tank alert/shutoff.

# Hisense

# 70 PINT

up to 500 sq.ft

**DEHUMIDIFIER BUILT-IN PUMP**

## TECHNICAL SPECIFICATIONS

### Performance

Hisense-Model	DH-70kP1SDLE
Dehumidification (Pints/24 hrs)	70 (DOE Test Procedure)
Heating Capacity	N/A
Coverage	Up to 500 sq. ft.
Refrigerant	R-410A
Noise Level in dB(A)	53 ~ 55 dB(A)

### Electrical

Voltage / Freq / Amps	115V/60Hz / 6.9 A
-----------------------	-------------------

### Control Features

Unit Control Type	Electronic
Fan Control	Button
Adj. Humidity Control	Yes
Display Type	LED
Continuous Run	Yes
Auto Dry	Yes
Manual Setting	(30% ~ 80%)
Timer-Clock	Yes
Fan Speeds	2 speeds (Lo, Hi, Auto)
Auto Bucket Shutoff	Yes
Pump Mode	Yes

### General Features

Auto Bucket Shutoff	Yes
Bucket Capacity	14.4 pints
Bucket Shutoff Capacity	11.6 pints
Garden Hose Connection	Yes
Washable Filters	Yes

### Accessories

Quick Connect Hose	Yes, included (9mm dia)
--------------------	-------------------------



### Approvals

Safety	UL, CUL
Energy	Energy Star / CEC
Parcel Shippable	Yes

### Shipping

Unit Dimension WxDxH (mm)	383 X 290 X 628
Carton Dimension WxDxH (mm)	435 X 336 X 668
Unit Dimension WxDxH (inch)	15 X 11.4 X 24.7
Carton Dimension WxDxH (inch)	17.1 X 13.3 X 26.3
Net Weight /Gross Weight (Kg)	20.9/23.7
Net Weight /Gross Weight (lbs)	46.0/52.3
Loading(40HQ)	746

### WARRANTY/UPC

Parts & Labor	2 years
UPC	854098003951

### Control panel

115 Volts  
60Hz  
15 A

All product, product specifications, and data are subject to change without notice to improve reliability, function, design or otherwise. ©2016 Hisense USA. All rights reserved

Hisense USA Corporation  
7310 McGinnis Ferry Road, Suwanee, GA, 30024  
1-888-935-8880  
[www.hisense-usa.com](http://www.hisense-usa.com)